

SOLAIRE CARPET TILE SPECIFICATION

Construction	Interloop Patterned Loop with Tipshear	Gauge	5/64
Yarn Content	Antron® type 6,6 nylon (SCS-EPP-01226, an Environmentally Preferable Product certified by SCS)	Yarn Type	Antron® Legacy™ nylon
Tufted Yarn Weight	22 oz./sq. yd.	Nominal Total Weight	134 oz./sq. yd.
Avg. Yarn Pile Height	.125"	Average Yarn Density	6,048
Backing System	Perma-tile Vinyl Backing System w/Recycled Content	Approximate Backing Thickness	0.12 inches
Tile Size	24" x 24"	Approximate Total Thickness	0.28 inches
Custom Colors	Custom colors available at minimum yardage. Please contact your Atlas sales associate.	Folder Name	Ville Des Lumières Collection
Approved Installation Methods*	Monolithic, Brick-monolithic, Quarter-turn *Installation methods not approved by Atlas are at the customer's discretion, but care should be exercised to avoid unwanted visual effects. Complete installation instructions are included with each shipment and should also be viewed at www.atlascarpetmills.com .		
General Guidelines	Chair pads are highly recommended under roller casters to preserve appearance and prevent accelerated wear. Walk-off mats are recommended at all entrances to minimize soiling. This carpet is intended only for use as a floor covering. Atlas will not assume any liability when this carpet is used in any other manner.		
Quality Assurance	All certified carpets of Antron® Lumena™ Solution Dyed type 6,6 nylon meet strict performance and construction standards of the Invista performance standards program assuring the highest quality carpet. The Antron® type 6,6 nylon polymer provides superior resistance to crushing, matting, stain penetration and wear.		
Soil Retardant	DuraTech®, a patented soil resistance technology, is only available on styles of Antron® type 6,6 nylon.		
Static Control	Antron® type 6,6 nylon carries a limited lifetime antistatic protection warranty not to exceed 3.5kV.		
Flammability Ratings	ASTM E648 Flooring Radiant Panel Test: Class I. ASTM E662 NBS Smoke Chamber Test; < 450 in the Flaming Mode.		
Indoor Air Quality	Certified by the Carpet and Rug Institute and assigned the Green Label Plus certification number GLP5300 .		
NSF-140 Certification	All Atlas carpet tiles are NSF-140 certified.		
Environmental	Atlas CARPET TILE, by total weight, contains over 33% recycled content; 23% post-industrial recycled content and 10% post-consumer recycled content. For complete details on contributions to LEED, please visit our website at www.atlascarpetmills.com .		
Warranty	Antron® type 6,6 nylon carries a Limited 10-Year Wear Warranty. See written warranties at www.atlascarpetmills.com.		
Additional Information	Pattern lines, inherent in the pattern and construction of this product, which may be visible lengthwise or widthwise, are not considered a manufacturing defect. Watermarking or shading, a pile reversal phenomenon that can occasionally occur in any carpet construction, regardless of fiber type, is not considered a manufacturing defect. The mill reserves the option of making minor modifications in specifications when necessary in order to improve performance and to accommodate changes in material supply or manufacturing processes.		
Trademarks	© INVISTA All Rights Reserved. Antron® and the Antron® family of marks and logos are trademarks of INVISTA. DuraTech® is a registered trademark for soil resistant treatment.		
© Copyright	This pattern is protected under federal copyright law and may not be duplicated without Atlas' express written permission.		

Atlas Carpet Mills

Plant, Offices and Showroom:

2200 Saybrook Avenue
Los Angeles, CA 90040
(323) 724-9000 (800) 372-6274
FAX (800) 272-8527 FAX (323) 724-4526

Chicago Showroom:

The Merchandise Mart
222 Merchandise Mart Plaza, Suite 1082
Chicago, IL 60654
(866) 527-9870 FAX (312) 527-9980

New York City Showroom:

New York Design Center
200 Lexington Ave., Suite 1314
New York, NY 10016
(800) 223-0323 FAX (212) 779-7905

Direct Access and Voice Mail: (800) 367-8188 (Ext: 2300 for SAMPLE and ORDER DESK)

www.atlascarpetmills.com