



Atlas

Grand Entrance Plank Carpet Tile Specification

Style Number	TM314
Yarn Content	Antron® Lumena DNA™ solution dyed type 6,6 nylon
Tufted Yarn Weight	20 oz./sq. yd.
Construction	Patterned Loop
Backing System	Perma-tile Vinyl Backing System w/Recycled Content
Tile Size	12" x 36"
Gauge	1/12
Pile Heights	.250" x .188" x .125" (6.35mm/4.78mm/3.18mm)
Yarn Type	Antron® Lumena DNA™ nylon
Nominal Total Weight	105 oz./sq. yd.
Average Yarn Density	4,981
Approximate Total Thickness	0.31 inches
Folder Name	Transitions

Recommended Installation Methods* Vertical Ashlar, Monolithic and Herringbone
*Installation methods are at the customer's discretion, but care should be exercised to avoid unwanted visual effects. Complete installation instructions are included with each shipment and should also be viewed at atlas carpetmills.com.

General Guidelines Chair pads are highly recommended under roller casters to preserve appearance and prevent accelerated wear. Walk-off mats are recommended at all entrances to minimize soiling. This carpet is intended only for use as a floor covering. Atlas will not assume any liability when this carpet is used in any other manner.

Quality Assurance All certified carpets of Antron® Lumena DNA™ solution dyed type 6,6 nylon meet strict performance and construction standards of the INVISTA performance standards program assuring the highest quality carpet. The Antron® type 6,6 nylon polymer provides superior resistance to crushing, matting, stain penetration and wear.

Soil Retardant Permanent build-in stain and soil protection.

Static Control Antron® Lumena DNA™ solution dyed type 6,6 nylon carries a limited lifetime antistatic protection warranty not to exceed 3.5kV.

Flammability Ratings ASTM E648 Flooring Radiant Panel Test: Class I. ASTM E662 NBS Smoke Chamber Test; < 450 in the Flaming Mode.

Indoor Air Quality Certified by the Carpet and Rug Institute and assigned the Green Label Plus certification number **GLP5300**.

NSF-140 Certification All Atlas carpet tiles are **NSF-140** certified.

Health Product Declaration Health Product Declaration (HPD) information can be found on the Atlas website in the Resources tab under Environmental.

Environmental Product Declaration Environmental Product Declaration (EPD) information can be found on the Atlas website in the Resources tab under Environmental.

Environmental Atlas Carpet Tile, by total weight, contains over 33% recycled content; **23% post-industrial recycled** content and **10% post-consumer recycled** content. For complete details on contributions to LEED, please visit our website at atlas carpetmills.com.

Warranty Antron® Lumena DNA™ solution dyed type 6,6 nylon carries a Limited 10-Year Wear Warranty. See written warranties at atlas carpetmills.com.

Additional Information Pattern lines, inherent in the pattern and construction of this product, which may be visible lengthwise or widthwise, are not considered a manufacturing defect. Watermarking or shading, a pile reversal phenomenon that can occasionally occur in any carpet construction, regardless of fiber type, is not considered a manufacturing defect. The mill reserves the option of making minor modifications in specifications when necessary in order to improve performance and to accommodate changes in material supply or manufacturing processes.

Trademarks © 2019 INVISTA - All Rights Reserved. Antron® and the Antron® family of marks and logos are trademarks of INVISTA.

©Copyright This pattern is protected under federal copyright law and may not be duplicated without Atlas' express written permission.

Find an Atlas Sales Associate at (800) 367-8188, or info@atlas carpetmills.com. Request a sample or place an order at (800) 367-8188

Main Office and Manufacturing
716 Bill Myles Drive
Saraland, AL 36571
T: (800) 372-6274

Chicago Showroom
222 Merchandise Mart Plaza, Suite 10-102
Chicago, IL 60654
T: (866) 527-9870

Washington DC Showroom
1156 15th Street, NW, Suite 603
Washington, DC 20005
T: (800) 367-0842